



Jiaxing Green Shield New Materials Co.,
 Ltd
 Add: No.365 West Qianjiang Road, Haining,
 Zhejiang, China

1050gsm 3loz PVC Knife Coated Membrane
Anti-UV, Color fastness, anti-mold, fungus, Rohs

| Properties | Units | Test method | Average value |
|------------------------------|-------------|--------------------|---------------------|
| Base Thread Density | Denier | DIN53350 | 1000*1000D |
| Base Fabric Density | Thread/inch | DIN53351 | 30*30 Panama |
| Finished Fabric Weight | Gram/m2 | DIN53352 | 1050 |
| Base Fabric Weight | Gram/m2 | DIN53352 | 265 |
| Thickness - finished product | um | DIN53352 | 80 |
| Break Strength Warp | N/5cm | GB/T1040 | 4200 |
| Break Strength Weft | N/5cm | GB/T1040 | 4000 |
| Tear Strength Warp | N/5cm | DIN 53363 | 600 |
| Tear Strength Weft | N/5cm | DIN 53363 | 550 |
| Adhension | N/5cm | DIN 53357 | 120 |
| Temperature range | °C | DIN 53368 | -30 ~ +70 |
| Flame retardancy | | Self-extinguishing | Both sides lacquing |