



Jiaxing Green Shield New Materials Co.,  
 Ltd  
 Add: No.365 West Qianjiang Road, Haining,  
 Zhejiang, China

**610gsm 18oz PVC Coated Fabric**  
**Anti-UV, Color fastness, anti-mold, fungus**

| Properties                   | Units       | Test method        | Average value |
|------------------------------|-------------|--------------------|---------------|
| Base Thread Density          | Denier      | DIN53350           | 1000D*1300D   |
| Base Fabric Density          | Thread/inch | DIN53351           | 18*17         |
| Finished Fabric Weight       | Gram/m2     | DIN53352           | 610           |
| Base Fabric Weight           | Gram/m2     | DIN53352           | 200           |
| Thickness - finished product | um          | DIN53352           | 55            |
| Break Strength Warp          | N/5cm       | GB/T1040           | 2800          |
| Break Strength Weft          | N/5cm       | GB/T1040           | 2600          |
| Tear Strength Warp           | N/5cm       | DIN 53363          | 280           |
| Tear Strength Weft           | N/5cm       | DIN 53363          | 260           |
| Adhension                    | N/5cm       | DIN 53357          | 120           |
| Temperature range            | °C          | DIN 53368          | -30 ~ +70     |
| Fire Retardant               |             | Self-extinguishing |               |