

Dry bags material-Factory wholesale



GSTARP

Good waterproof performance wear resistance and tear strength lightweight and durable



WEB: www.gstarp.com

Jiaying Green Shield New Materials Co., Ltd



GSTARP

Dry bags material–Factory wholesale

PVC dry bag fabric offers exceptional waterproof performance, abrasion resistance, and tear strength, providing protection for items from moisture and stains even in extreme environments. Lightweight and durable, it is perfect for outdoor adventures, marine activities, and daily use. Whether protecting electronic devices, clothing, or valuables, this fabric offers reliable protection. Its flexibility, ease of cleaning, and low maintenance make it an ideal choice for making dry bags, ensuring both safety and convenience for users.

Professional sales team, over 15 years experience in producing Dry bags material, Over 10 years OEM&ODM finished product experience, we are a factory produces pvc tarpulin in Haining ,The greatest feature of our Tarp for Dry bags material is stable and durable quality.



Welcome to
OURFACTORY



You can get the reasonable price with best quality here.



GSTARP

Dry bags material–Factory wholesale

Properties of PVC Dry bags material:

- ▶ Vivid colour
- ▶ Antibacteria
- ▶ Self cleaning
- ▶ Uv resistance
- ▶ Fire retardent
- ▶ 100%waterproof
- ▶ Folding resistant
- ▶ No phthalic acid
- ▶ Puncture resistant
- ▶ Alcohol resistance
- ▶ Corrosion resistance
- ▶ Dimensional stability
- ▶ Softness and excellent hand feel



Durability:

The PVC coated fabric is produced by imported equipment, the product structure is advanced, has a solid surface, has a strong resistance to prevent tear, this is one of the biggest features of our products, the quality is very stable,with long life cycle, there is a very excellent durability.

Scratch resistant:

The PVC coated fabric is a kind of liquid PVC uniformly coated on top of the base cloth, the upper and lower two two surfaces are smooth and strong, and polyester base cloth on the high strength, can prevent sharp objects scratch or puncture, with good scratch resistance.

Wear-resistant:

The fabric surface is very smooth, the surface coating is arranged tightly via surface acrylic or PVDF treatment techniques, the hardness is very high, resisting all kinds of wear and tear, so it is very wear-resistant.

Smooth surface:

The graphic cloth is made by lamination or coating, and with the special treatment on the surface, the surface is very smooth.



corrosion preventive



Recyclable



printable



heat insulation



GSTARP

Dry bags material–Factory wholesale

Items	polyester fabric	weight(g/sqm)
GLT1101	1000D*1000D 30*30	750
GLT1102	1000D*1000D 20*20	680
GLT1103	1000D*1000D 20*20	650
GLT1104	1000D*1000D 20*20	610
GLT1105	1000D*1000D 9*9	580
GLT1106	1000D*1000D 18*18	550
GLT1107	500D*840D	450
GCT2203	1000D*1000D 23*23	850
GCT2204	1000D*1000D 23*23	750
GCT2205	1000D*1000D 20*20	680
GCT2206	1000D*1000D 20*20	650
GCT2207	1000D*1000D 20*20	700
GCT2208	1000D*1000D 20*20	610
GKCT3305	1000D*1000D 20*20	650
GKCT3305	1000D*1000D 20*20	610

Colour: Any color





GSTARP

Dry bags material–Specifications

Properties	Units	Test method	450gsm	500gsm	550gsm	590gsm	610gsm	650gsm	680gsm	750gsm
			Average value	Average value	Average value	Average value	Average value	Average value	Average value	Average value
Base Thread Density	Denier	DIN53350	500D*500D	1000D*1000D	1000D*1000D	1000D*1000D	1000D*1000D	1000D*1000D	1000D*1000D Low-wick	1000D*1000D
Base Fabric Density	Thread/inch	DIN53351	18*16	20*20	18*18	9*9	14*14	20*20	20*20	23*23
Finished Fabric Weight	Gram/m2	DIN53352	580	500	550	600	610	650	680	750
Base Fabric Weight	Gram/m2	DIN53352	95	172	157	50	125	175	175	200
Thickness–finished product	um	DIN53352	54	40	42	1300	52	52	52	60
Break Strength Warp	N/5cm	GB/T1040	1500	2000	2000	25	1800	2500	2500	3000
Break Strength Weft	N/5cm	GB/T1040	1200	1800	1800	1100	1600	2200	2200	2800
Tear Strength Warp	N/5cm	DIN 53363	250	250	220	25	200	280	280	300
Tear Strength Weft	N/5cm	DIN 53363	200	220	200	300	180	250	250	270
Adhesion	N/5cm	DIN 53357	50	120	120	280	80	90	90	120
Temperature range	°C	DIN 53368	-30~+70	-30~+70	-30~+70	-30~+70	-30~+70	-30~+70	-30~+70	-30~+70
Fire Retardant		Self-extinguishing							Both sides lacquering	Both sides lacquering

Jiaxing Green Shield New Materials Co., Ltd

Mobile: 0086 13625863196

WhatsApp: 0086 13625863196

Add : No.365 West Qianjiang Road, Haining, Zhejiang, China

e-mail : bill@gstarp.com