

PVC water tank fabric Available Worldwide



GSTARP



PVC water tank fabric also called PVC water bag, vinyl water fabric, It' s a heavy duty tarpaulin, the best feature is high strength, 100% waterproof and durable. It can be made into flexible water tanks and cube water tanks, also can be used with containers and trailers. It has very good environmental adaptability, resist harsh environment, especially chemical corrosion with very good UV resistance performance. It can be used in emergency water supply, desert, construction site, military and other fields. Meanwhile, it can be filled with water, oil, all kinds of chemicals, biogas and other gases, and also drinking water.

water tank fabric Available **Worldwide**

WEB: www.gstarp.com

Jiaying Green Shield New Materials Co., Ltd

PVC water tank fabric Available Worldwide




GSTARP

GSTARP is a professional factory produces PVC water tank fabric with over 15 years of experience. Our products are sold to more than 150 countries around the world. We can produce PVC water tank fabric with weights ranging from 650g to 2700g, with a maximum width of 5.1 meters. We can produce any color according to RAL, PANTONE, or sample. Width and length can also be made according to customer requirements.


Hot sale 650gsm 850gsm 900gsm 930gsm 1000gsm 1450gsm 2000gsm 2700gsm

Professional sales team, Over 10 years OEM&ODM finished product experience, Gemeny production lines, Automatic computer colour meching system, Advanced inspection process, Imported pvc resin, Can deliver what exactly client need.





Width and length can also be made according to customer requirements

PVC colorful



PVC Purpose



PVC Features of PVC bag fabric



Anti-static

fabri is completely anti-static, this is very important for safety, all purchasing German production equipment, anti-static level is 10E7.



Anti static

Long lifetime

Produced by coating or coating process, the product structure is stable, quality is stable, with strong durability, to ensure economic returns, the product has a very good service life, over 10years.



long-life

Recyclable

PVC Tarpaulin all substances are degradable, including the production of auxiliary materials, and it is no harmful substances, fully recyclable.



Recyclable

Weldable

Laminated coated fabrics and coating coated fabrics are two layers of PVC film laminated on top of the base cloth in the center, both top and bottom surfaces are PVC layer, so it is very easy to weld, we usually use hot air welding and high frequency welding machine to weld firmly with very good results.



welding

Environmental Protection

GSTARP follow the EU environmental standards and the U.S.HSF standards, all raw materials and auxiliary materials are strictly in accordance with the requirements of the test, our equipment is very advanced, to ensure that the entire production process is very environmentally friendly, our products are exported to more than 100 countries in the world, very environmentally friendly.



Environmental adaptability

Anti-puncture

fabric is five layers structure, each layer is high strength laminated price, and the surface is smooth, anti-puncture effect is very good



puncture protection



PVC Features of PVC bag fabric



GSTARP

| Properties | Units | Test method | 650sm | 850gsm | 900gsm | 1050sm | 1100gsm | 1250gsm | 1350gsm |
|------------------------------|---------------------|--------------------|---------------|---------------|---------------|-----------------------|-------------------|---------------|----------------------------------|
| | | | Average value | Average value | Average value | Average value | Average value | Average value | Average value |
| Base Thread Density | Denier | DIN53350 | 1000D*1000D | 500D*500D | 1000D*1000D | 1000D*1000D | 1300D*1300D | 1500D*1500D | 1500D*1500D |
| Base Fabric Density | Thread/inch | DIN53351 | 20*20 | 18*17 | 28*26 | 30*30 Panama | 30*30 Panama | 30*30 Panama | 30*30 Panama |
| Finished Fabric Weight | Gram/m ² | DIN53352 | 650 | 850 | 900 | 1050 | 1100 | 1250 | 1350 |
| Base Fabric Weight | Gram/m ² | DIN53352 | 175 | 75 | 236 | 265 | 320 | 380 | 380 |
| Thickness – finished product | um | DIN53352 | 52 | 65 | 72 | 80 | 88 | 100 | 106 |
| Break Strength Warp | N/5cm | GB/T1040 | 2500 | 1250 | 3500 | 4200 | 5500 | 7000 | 7000 |
| Break Strength Weft | N/5cm | GB/T1040 | 2200 | 1150 | 3300 | 4000 | 5000 | 6800 | 6800 |
| Tear Strength Warp | N/5cm | DIN 53363 | 280 | 150 | 500 | 600 | 700 | 1000 | 1000 |
| Tear Strength Weft | N/5cm | DIN 53363 | 250 | 125 | 450 | 550 | 700 | 900 | 900 |
| Adhesion | N/5cm | DIN 53357 | 90 | 100 | 120 | 120 | 120 | 120 | 120 |
| Temperature range | °C | DIN 53368 | -30~+70°C | -30~+70°C | -30~+70°C | -30~+70°C | -30~+70°C | -30~+70°C | A Grade |
| Flame retardancy | | Self-extinguishing | | | Top side | Both sides lacquering | TRIPLE LACQUERING | | PVDF(unwektable) /PVDF(wektable) |

Jiaxing Green Shield New Materials Co., Ltd

Mobile: 0086 13625863196

WhatsApp: 0086 13625863196

Add : No.365 West Qianjiang Road, Haining, Zhejiang, China

e-mail : bill@gstarp.com

WEB: www.gstarp.com